

Official Gazette for Kokai Patent Applications, Front Page

(11) Publication no.: Unexamined Patent Application Publication No. H05-211021

(43) Disclosure date: August 20, 1993

(51) Int. Cl.⁵ H01H 21/00 330

13/52

(21) Application no.: Patent Application No. H04-183002

(22) Application date: June 17, 1992

(71) Applicant: MIC Electron Co.

(72) Inventor(s): Tomoyoshi Miyata
Shinji Hasegawa
Tomoshi Myojin

(30) Priority

Priority claim nos.: 1991198492 Priority dates: July 13, 1991 Priority claim states: JP

1991293644 Oct. 14, 1991 JP

1991293645 JP

(54) Push Switch

(57) [Abstract] (amended)

[Purpose] Relates to a push switch whose contact is switched ON/OFF by depressing/releasing a pushing means.

[Constitution] A push switch constituted such that it is equipped with a horizontal U-shaped spring piece A in which are formed upper contact piece 3a and lower contact piece 3b, which is longer than the said upper contact piece 3a, by bifurcating the lower piece 3 of a spring piece composed of upper piece 1, recurved part 2, and lower piece 3, and [with] a pushing means 4 that pushes and rotates a holder B with a fulcrum shaft 5 as the center, on the end part of the upper plate 4a; [it] is equipped with a fulcrum shaft 5 at the center of the horizontal U-shaped part 4b; a contact spring piece C is provided with the holder B and the horizontal U-shaped spring piece A as a unit; the said contact spring C is pivoted rotatably with its fulcrum shaft 5 at a set position in case D and the like; the lower contact piece 3b is pressure-welded to one fixed contact 7b; [it] is installed in the state such that the upward rotary force of the holder B resulting from its elastic restorative force is absorbed when the upper plate 4a of the holder B strikes the stopper part 14; and the end of the upper contact piece 3a is positioned at predetermined distance d above the other fixed contact 7a.

